






Diverse Gewinde
Diverse threads
Filetages diverses
Filettature varie

NPT
NPTF
NPSM
NPSF
Pg
MF




Rp
Rc
Rd
BSF
W keg
MJ

*This design is also suitable for blind holes, e.g. according DIN 19212.
L'esecuzione è adatta anche per fori ciechi per es DIN 19212.*

Bestell-Nr. / Cat. No. / No. de Cat. / Cat. Nr.									6100/7100	6110/7110	6102/7102	6112/7112	6605/7605	6645/7645
Typ / Type / Type / Tipo									TWIN ST	TWIN ST AZ	TWIN VG	TWIN VG AZ	SALOREX VA	SALOREX VA
NPT ANSI/ASME B 1.20.1 														
DIN 371 														
DIN 374 														
Lochform / Hole type / Types de trous / Forma dei fori														
Oberfläche / Surface / Surface / Superficie													vap	TiN
Toleranz / Tolerance / Tolérance / Tolleranza									-	-	-	-	-	-
Anschnitt-Form / Chamfer form / Forme d'entrée / Forma d'imbocco									C / 2-3	C / 2-3	C / 2-3	C / 2-3	C / 2-3	E / 1,5-2
	d ₁	- P/1"	l ₁	l ₂	l ₃	d ₂	a		HSSE	HSSE	HSSE	HSSE	HSSE	HSSE
DIN 371	1/16	- 27	90	12	26	8	6,2		6100A1732	6110AAIAA	6102A1884	6112A1888	6605AAHAA	
	1/8	- 27	90	12	26	10	8		6100A1733	6110AAJAA	6102A1885	6112A1887	6605AAIAA	6645AFGAA
	1/4	- 18	100	18	34,5	14	11		6100F0007	6110AAKAA	6102A1886	6112A1898	6605AAJAA	6645AFHAA
DIN 374	1/16	- 27	90	12	-	6	4,9			7110AAIAA				
	1/8	- 27	100	12	-	7	5,5			7110AAJAA				
	1/4	- 18	100	18	-	11	9			7110AAKAA				
	3/8	- 18	110	18	-	14	11		7100AIGAB	7110AAMAA	7102A1890	7112A1896	7605F0001	7645A1950
	1/2	- 14	140	23	-	16	12		7100AIEAH	7110AANAA	7102A1891	7112A1893	7605F0003	7645A1951
	3/4	- 14	150	24	-	20	16		7100AIFAE	7110AAPAA	7102A1892	7112A1894	7605A5086	
	1	- 11,5	170	30	-	25	20		7100AIHAD		7102A1889	7112A1895	7605A5088	
	1 1/4	- 11,5	190	32	-	32	24						7605A5089	
	1 1/2	- 11,5	200	32	-	36	29						7605A5090	
	2	- 11,5	220	34	-	45	35							
Einsatzgebiete / Range of application									A	1.1-1.2	1.3-1.4	1.3-1.4	1.2-1.3	1.2-1.5
Utilisations / Campo d'impiego									R			1.1-1.2	1.1-1.2	1.1-1.2
									F		1.1-2.1	1.1-2.1		
									N	1.4/2.3	1.4/2.3	1.4/2.3-2-5		
									S					
									H					



[illegible]

Bestell-Nr. / Cat. No. / No. de Cat. / Cat. Nr.								6100/7100	6102/7102	6605/7605			
Typ / Type / Type / Tipo								TWIN ST	TWIN VG	SALOREX VA			
NPTF ANSI/ASME B 1.20.3 													
DIN 371 													
DIN 374 													
Lochform / Hole type / Types de trous / Forma dei fori													
Oberfläche / Surface / Surface / Superficie										vap			
Toleranz / Tolerance / Tolérance / Tolleranza								-	-	-			
Anschnitt-Form / Chamfer form / Forme d'entrée / Forma d'imbocco								C / 2-3	C / 2-3	C / 2-3			
DIN 371	d ₁	- P/1"	l ₁	l ₂	l ₃	d ₂	a	HSSE	HSSE	HSSE			
	1/16	- 27	90	12	26	8	6,2	6100A1740	6102A1899	6605AANAA			
	1/8	- 27	90	12	26	10	8	6100A1741	6102A1900	6605AAPAA			
	1/4	- 18	100	18	34,5	14	11	6100A1742	6102A1901	6605AAQAA			
DIN 374	3/8	- 18	110	18	-	14	11	7100A1743	7102A1905	7605A5096			
	1/2	- 14	140	23	-	16	12	7100A1744	7102A1904	7605A5098			
	3/4	- 14	150	24	-	20	16	7100A1745	7102A1903	7605A5099			
	1	- 11,5	170	30	-	25	20			7605A5102			
	1 1/4	- 11,5	190	32	-	32	24			7605A5103			
	1 1/2	- 11,5	200	32	-	36	29	7100A1746	7102A1902	7605A5101			
	2	- 11,5	220	34	-	45	35			7605A5104			
Einsatzgebiete / Range of application								A	1.1-1.2	1.3-1.4	1.2-1.3		
Utilisations / Campo d'impiego								R			1.1-1.2		
								F		1.1-2.1			
								N	1.4/2.3	1.4/2.3			
								S					
								H					



Bestell-Nr. / Cat. No. / No. de Cat. / Cat. Nr.

Typ / *Type* / *Type* / *Tipo*


7100

TWIN ST


7642

**SALOREX
UNI**

NPSM
ANSI B 1.20.1



≈ **DIN 5156**


$$b_2 \approx 10 \times p$$

Lochform / *Hole type* / *Types de trous* / *Forma dei fori*

max. 2 x D

max. 3 x D

Oberfläche / *Surface* / *Surface* / *Superficie*

vap

Toleranz / *Tolerance* / *Tolérance* / *Tolleranza*

X

Anschnitt-Form / Chamfer form / Forme d'entrée / Forma d'imbocco

C / 2-3

E / 1,5-2

d ₁	- P/1"	l ₁	l ₂	d ₂	a		HSSE	HSSE				
1/8	- 27	90	18	7	5,5	9,1	7100AF7AA	7642A1937				
1/4	- 18	100	22	11	9	12	7100AF8AA	7642A1938				
3/8	- 18	100	22	12	9	15,5	7100AGEAA	7642A1939				
1/2	- 14	125	25	16	12	19	7100AGFAA	7642A1941				
3/4	- 14	140	28	20	16	24,5	7100AGDAA	7642A1940				
1	- 11,5	160	30	25	20	30,5	7100AF9AA					

Einsatzgebiete / *Range of application*
Utilisations / *Campo d'impiego*

A

1.1-1.3

1.1-1.4

R

1.1

F

N

S

H

[illegible]

144 Das Pg Gewinde wird nur noch für Reparaturbedarf verwendet. Ein Beschluß der VDE (DKE)-Kommission.
Le filetage PG ne reste plus utilisé qu'en cas de réparation. Décision de la commission VDE (DKE)

[illegible]

Bestell-Nr. / Cat. No. / No. de Cat. / Cat. Nr.

Typ / *Type* / *Type* / *Tipo*

7100


TWIN ST

7642


**SALOREX
UNI**

Rp (BSPP)

DIN EN 10226-1, ISO 7-1



DIN 5156


$$l_2 \approx 10 \times P$$

Lochform / *Hole type* / *Types de trous* / *Forma dei fori*

max. 2 x D

max. 3 x D

Oberfläche / *Surface* / *Surface* / *Superficie*

vap

Toleranz / *Tolerance* / *Tolérance* / *Tolleranza*

X

—

Anschnitt-Form / *Chamfer form* / *Forme d'entrée* / *Forma d'imbocco*

C / 2-3

E / 1,5-2

d ₁	- P/1"	l ₁	l ₂	d ₂	a		HSSE	HSSE				
1/16	- 28	90	17	6	4,9	6,55						
1/8	- 28	90	18	7	5,5	8,6	7100AFYAA	7642A1911				
1/4	- 19	100	22	11	9	11,5	7100AFZAA	7642A1910				
3/8	- 19	100	22	12	9	15	7100AF0AA	7642A1909				
1/2	- 14	125	25	16	12	18,5	7100AF1AA	7642A1908				
3/4	- 14	140	28	20	16	24	7100AF2AA	7642A1907				
1	- 11	160	30	25	20	30,25	7100AF3AA	7642A1906				

Einsatzgebiete	/ Range of application							
----------------	------------------------	--	--	--	--	--	--	--

Utilisations / Campo d'impiego

A

1.1-1.3

1.1-1.4

R

1.1




F

2.1

N

S

H

Bestell-Nr. / Cat. No. / No. de Cat. / Cat. Nr.								5100	7100				
Typ / Type / Type / Tipo								TWIN ST kurz	TWIN ST				
Rc (BSPT) DIN EN 10226-2, ISO 7-1 													
DIN 2181 ≈													
DIN 374 ≈													
Lochform / Hole type / Types de trous / Forma dei fori													
Oberfläche / Surface / Surface / Superficie													
Toleranz / Tolerance / Tolérance / Tolleranza								-	-				
Anschnitt-Form / Chamfer form / Forme d'entrée / Forma d'imbocco								C / 2-3	C / 2-3				
	d ₁	- P/1"	l ₁	l ₂	d ₂	a		HSSE	HSSE				
DIN 2181 ≈	¹ / ₁₆	- 28	63	12	6	4,9		5100A1925 5100A1924 5100A1923 5100A1922 5100A1921 5100A1920					
	¹ / ₈	- 28	63	12	7	5,5							
	¹ / ₄	- 19	63	18	11	9							
	³ / ₈	- 19	70	18	12	9							
	¹ / ₂	- 14	80	23	16	12							
	³ / ₄	- 14	100	24	20	16							
	1	- 11	110	30	25	20							
DIN 374 ≈	¹ / ₈	- 28	100	12	7	5,5		7100AGHAA 7100AGIAA 7100AGJAA 7100AGKAA					
	¹ / ₄	- 19	100	18	11	9							
	³ / ₈	- 19	110	18	14	11							
	¹ / ₂	- 14	140	23	16	12							
	³ / ₄	- 14	150	24	20	16							
	1	- 11	170	30	25	20							
	1 ¹ / ₄	- 11	190	32	32	24							
	1 ¹ / ₂	- 11	200	32	36	29							
	2	- 11	220	34	45	35							
Einsatzgebiete / Range of application Utilisations / Campo d'impiego								A	1.1-1.3	1.1-1.3			
								R					
								F	2.1	2.1			
								N					
								S					
								H					



[illegible]

[illegible]

